

ABSTRACT OF THE DISCLOSURE

5

A device for sealing and anchoring within a tubular member. The device comprises a top swage member disposed within the tubular member, with the top swage member having a longitudinal center of axis. Also included is a first sealing member disposed about the top swage member, with the first sealing member containing a first plurality of circumferential ribs disposed about the first sealing member. The device may also include a second sealing member that is attached to the first sealing member, with the second sealing member containing a second plurality of circumferential ribs disposed about the second sealing member. A bottom swage member is disposed within the second sealing member, with the bottom swage member having a longitudinal center of axis. The device further comprises a setting apparatus for driving the top swage longitudinally downward relative to the top swage's longitudinal center axis and for driving the bottom swage longitudinally upward relative to the bottom swage's center axis. In the preferred embodiment, the top swage member has a first cylindrical surface that extends to a second conical surface, and wherein the first cylindrical surface is disposed within the first sealing member. Additionally, the bottom swage member will have a first cylindrical surface that extends to a second conical surface, with the first cylindrical surface being disposed within the second sealing member. A method of anchoring and sealing a device within a tubular member is also included.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500

20